Philips
Composite A/V cable

9 ft

SWV3213W

9ft/2.8m
Stereo audio + composite video cables
Câble audio stéréo y câble vidéo composant
Cable para vídeo compuesto y sonido estereofónica
24k Gold
PHILIPS

Turn up your viewing experience

with this composite audio/video cable

Step up to a better audio/video connection between components.

Protects against signal loss
- Copper braided reinforced aluminum shielding

Enjoy better picture/sound quality
- 24 carat gold-plated connectors optimize signal
- High purity copper conductor for reliable signal transfer

Easy installation
- Color coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability
- Flexible PVC jacket
- Rubber strain relief
- Protective metal shell for extended durability

PHILIPS
sense and simplicity

Composite A/V cable
9 ft

SWV3213W/27

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 19.7 x 26.7 x 3.2 cm
- Nett weight: .181 kg
- Gross weight: .227 kg
- Tare weight: .046 kg

Outer Carton
- Outer carton (L x W x H): 27.9 x 20.3 x 12.7 cm
- Nett weight: .724 kg
- Gross weight: 2.268 kg
- Tare weight: 1.544 kg

Highlights

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief
Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

Braided shielding
Copper braided reinforced aluminum shielding protects against signal loss and interference.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

High purity copper
This copper conductor provides high accuracy in signal transfer with minimal resistance.

Issue date 2009-11-06

Version: 1.0.5

12 NC: 8670 000 37035
UPC: 6 09585 14821 5

© 2009 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com